



Yes, you can:

Tel: 01656 776222 Fax: 01656 776220
Email: ordersuk@invacare.com
Online Spares available at: www.invacare.co.uk

JANUARY 2021
Customer Ref:

Customer Ref* Account No*
Contact No* Order No*
Delivery Address* Order Qty*
Order date*

M90 AVIVA RX20 Standard seating

Standard Features

- Max user weight 136kg
Crash tested ISO 7176 -Part 19
One piece seat plate width 380mm (15") or 430mm (17") with standard foam cushion (50mm, 2")
seat depths 410mm - 510mm (16" - 20")
Tension adjustable backrest
Standard T-Armrests, detachable with short armpad
Powered "fixed pivot" Tilt 20°
Manual settable backrest Recline (0° - 30°, in 3.75° steps)
80° hangers with fixed footplate
Remote LiNX DLX-REM211 with standard Bracket
Choice of 5 Shroud colours, 5 Rim insert colours
8" (200 mm) x 2.50-4 (65 mm) Castor, puncture proof solid tyre
14" Drive wheel (355 mm) x 3" (75 mm), Solid inlay Dual density foam insert
CTC Suspension Control - Traction - Comfort
6 km/h 4 pole Durawatt motors
52Ah batteries
8A (200 - 250V) charger
Anti tippers
4 Point tie down system
Lapbelt with autolock

Standard Base price: £3,335



Please make your selection with a cross in the box ○ Free of charge ◆ standard feature POA special request

Customer weight = KG

Table with columns: Code, Description, Price. Rows include BASE MODEL* (JBB0000, JBX1300), CHASSIS WIDTH* (JBL2810), and SEATING TYPE* (JBB2105).

SEAT FRAME*			
JBB2110	<input type="checkbox"/>	One Piece Seat Plate	◆
SEAT WIDTH*			
JBB2121	<input type="checkbox"/>	380 mm Seat Plate	○
JBB2122	<input type="checkbox"/>	430 mm Seat Plate	◆
SEAT DEPTH*			
JBB2132	<input type="checkbox"/>	Seat Depth 410 mm	○
JBB2134	<input type="checkbox"/>	Seat Depth 460 mm	○
JBB2136	<input type="checkbox"/>	Seat Depth 510 mm	○
SEAT CUSHION*			
JBB2141	<input type="checkbox"/>	Standard Foam Cushion 50 mm height	◆
JBB2140	<input type="checkbox"/>	Without seat cushion	○
BACKREST SUPPORT*			
JBB2161	<input type="checkbox"/>	Backrest frame, detachable, height 480 mm For Tension Adjustable Upholstery/Matrix Backs	◆
BACKREST UPHOLSTERY / CUSHION*			
JBB2171	<input type="checkbox"/>	Tension Adjustable Upholstery nylon overlay short = 480 mm / 7 straps measured from seat plate to top of upholstery 480 mm	◆
UPHOLSTERY TYPE*			
JBB2151	<input type="checkbox"/>	Black Fabric Upholstery (Nylon w 2141; 2-way-stretch material w 2142, 2143)	◆
ARMREST (Pair)*			
JBB2191	<input type="checkbox"/>	T-Arm detachable, Standard Adjustment range from seat plate: 245 - 315 mm	◆
ARMPAD (Pair)*			
JBB2195	<input type="checkbox"/>	Short Armpad (325 mm)	◆
HEADREST / NECKREST - Adequate headrest option must be selected*			
JBB1495	<input type="checkbox"/>	Non Invacare Headrest - no mounting hardware With Backbrace/Pushbar dia. 22mm in conjunction with telescopic seat frame/backposts	◆
SEAT LIFTER / SEAT TILT*			
JBB1092	<input type="checkbox"/>	Powered "fixed pivot" Tilt 20°	◆
SEAT T GROUND HEIGHT*			
JBB2857	<input type="checkbox"/>	Seat-to-Floor Height 435 mm	○
JBB2858	<input type="checkbox"/>	Seat-to-Floor Height 460 mm	○
JBB2859	<input type="checkbox"/>	Seat-to-Floor Height 485 mm	○
BACKREST RECLINER*			
JBB0975	<input type="checkbox"/>	Manual Settable Recliner (in 3.75° steps) 90° - 120°	◆
FOOTREST HANGER TYPE*			
JBB0526	<input type="checkbox"/>	Standard hanger 80° pair Lower leg length: 350 - 450 mm	◆
FOOTPLATE TYPE*			
JBB0512	<input type="checkbox"/>	Fixed Footplate pair	◆
CONTROLS*			
JBB2203	<input type="checkbox"/>	Remote LiNX DLX-REM211 = Drive & Actuators 3 Drive functions and power module incl. 2 Actuators	◆

CONTROL BRACKETRY*			
JBB1207	<input type="checkbox"/>	Standard Bracket RH	○
JBB1208	<input type="checkbox"/>	Standard Bracket LH	○
JBB1707	<input type="checkbox"/>	Swing Away Bracket RH	£121
JBB1708	<input type="checkbox"/>	Swing Away Bracket LH	£121
SHROUD COLOUR*			
JBB2871	<input type="checkbox"/>	Mid range - Black/Anthracite Shroud	○
JBB2872	<input type="checkbox"/>	Mid range - Silver Shroud	○
JBB2873	<input type="checkbox"/>	Mid range - Bengal Red Shroud	○
JBB2874	<input type="checkbox"/>	Mid range - Mercury Blue Shroud	○
JBB2875	<input type="checkbox"/>	Mid range - Midnight Purple Shroud	○
JBX0299	<input type="checkbox"/>	Premium - Individual Shroud Colour (includes coloured spreader bars on Modulite back) RAL number required Extended lead lime: + 15 days	£195
RIM COLOUR*			
JBB2882	<input type="checkbox"/>	Mid range - Black Rim Inserts	○
JBB2883	<input type="checkbox"/>	Mid range - Silver Rim Inserts	○
JBB2884	<input type="checkbox"/>	Mid range - Bengal Red Rim Inserts	○
JBB2885	<input type="checkbox"/>	Mid range - Mercury Blue Rim Inserts	○
JBB2886	<input type="checkbox"/>	Mid range - Midnight Purple Rim Inserts	○
FORKS*			
JBB2632	<input type="checkbox"/>	Double sided fork Without castor rim insert (enlarges wide base to 656 mm)	◆
FRONT WHEEL*			
JBB0828	<input type="checkbox"/>	8" (200 mm) x 2.50-4 (65 mm) Castor, puncture proof solid tyre	◆
DRIVE WHEEL*			
JBB0704	<input type="checkbox"/>	DW 14" (355 mm) x 3" (75 mm), Pneumatic	○
JBB0705	<input type="checkbox"/>	DW 14" (355 mm) x 3" (75 mm), Solid inlay Dual density foam insert	◆
C.T.C SUSPENSION*			
JBB2870	<input type="checkbox"/>	CTC Suspension Control - Traction - Comfort	◆
SUSPENSION SETTING*			
JBB1910	<input type="checkbox"/>	Soft (suggested for up to 70 kg User Weight)	◆
JBB1912	<input type="checkbox"/>	Medium (suggested for up to 90 kg User Weight)	○
JBB1911	<input type="checkbox"/>	Firm (suggested for up to 110 kg User Weight)	○
JBB1915	<input type="checkbox"/>	Very firm (suggested for up to 136 kg User Weight)	○
MOTOR TYPE*			
JBB1282	<input type="checkbox"/>	6 km/h	◆
BATTERY TYPE*			
JBB2860	<input type="checkbox"/>	52 Ah AGM (Top-Gel)	◆
CHARGER*			
JBB1343	<input type="checkbox"/>	Opti Charge Charger 8A (IP44)	◆
ANTI-TIPPERS*			
JBB1205	<input type="checkbox"/>	Anti-tipper	◆
TRANSPORTATION KIT*			
JBB1494	<input type="checkbox"/>	4-Point tie-down (Tested version for using wheelchair as a vehicle seat according to ISO 7176-19) Adequate headrest is compulsory	◆

LAP BELT*

JBB1329

Lap belt with Auto Lock Standard mount on backrest



TOTAL PRICE

Non Conforming Options:



For a more complex customer requirement please refer to our Invacare Unique special order form. email specialsuk@invacare.com or Fax: 01656 776220

Special Instructions

Please supply the following information:

Name: _____ Email: _____

Phone: _____ Fax: _____

Description of special request (please include relevant option code or part number):