

Motability Retail Prescription Form

Yes, you can:

Tel: 01656 776222 Email: ordersuk@invacare.com Online Spares available at: www.invacare.co.uk JAN-MAR 2024 Customer Ref:

Customer Ref*	Account No*
Contact No*	Order No*
Delivery Address*	Order Qty*
	Order date*

AVIVA RX40 Modulite M24 707026 - weekly Price £51.45

Standard Features

- Max user weight 136kg
- Crash tested ISO 7176 -Part 19
- Modulite seating system
- Tension adjustable backrest
- Standard T-Armrests, detachable with long armpad
- Manually settable Seat Tilt 0 15°
- Manual settable backrest Recline (0°- 30°, in 3.75°steps)
- 80° hangers with fixed footplate
- LiNX Control REM216 with swing away Bracket
- 9" Castor, puncture proof solid tyre
- Solid inlay Dual density foam insert
- 12 km/h Últra High Speed Package
- LED Light system with Indicators, 30 Lux headlights

Please make your selection with a cross in the box

- 73,5 Ah Gel Batteries
- Anti tippers
- 4 Point tie down system
- Lapbelt with autolock (adjustable both sides)

Standard Base price: £7,424



standard feature POA special request

Customer weig	ght = KG	
Code	Description	
BASE MODEL*		
JBF0001	AVIVA RX 40 Base Model Max user weight up to 136 kg includes Performance Package: 120A Power Module + minimum 60 Ah Batteries	£7,424
CHASSIS WIDT	TH*	
JBL2810	Chassis Narrow (560 mm/22")	•
SEATING TYPE	<u></u>	
JBF2100	Invacare® Modulite Seat Unit	•

O Free of charge

SEAT FRAME*		
JBF2111	Telescopic Seat Frame and Plate with Side Rails width 380 to 530 mm Additional 50 mm by arms	0
JBF2112	Telescopic Seat Frame + Sling Seat with Side Rails width 380 to 530 mm; + 30 mm seat height Additional 50 mm by arms	0
SEAT WIDTH*		
JBF2121	380 mm Seat Plate Can be reduced to 330 mm in combination with inrigged armrests	O
JBF2122	430 mm Seat Plate Can be reduced to 380 mm in combination with inrigged armrests	O
JBF2123	480 mm Seat Plate	O
JBF2124	530 mm Seat Plate	O
SEAT DEPTH*		
JBF2132	Seat Depth 410 mm	O
JBF2134	Seat Depth 460 mm	0
JBF2136	Seat Depth 510 mm	O
SEAT CUSHION	*	
JBF2142	Matrx Flo-tech Cushion Flo-tech Lite	•
BACKREST SU	IPPORT*	
JBF2163	Backposts short (480 mm) For Tension Adjustable Upholstery/Matrx Backs, measured from seat plate to top of upholstery Width adjustable cast bracket	•
JBF2162	Backposts tall (540 mm) For Flex3 backrests/Tension Adjustable Upholstery/Matrx Backs, measured from seat plate to top of upholstery Width adjustable cast bracket	O
BACKREST UP	PHOLSTERY / CUSHION*	
JBF2171	Tension Adjustable Upholstery nylon overlay short = 480 mm / 7 straps measured from seat plate to top of upholstery 480 mm	•
UPHOLSTERY	TYPE*	
JBF2151	Black Fabric Upholstery (Nylon w 2141; 2-way-stretch material w 2142, 2143)	•
ARMREST (Pai	r)*	
JBF2191	T-Arm detachable, Standard Adjustment range from seat plate: 245 - 315 mm	•
ARMPAD (Pair)	*	
JBF2196	Long Armpad (375 mm)	•
SEAT LIFTER /	SEAT TILT*	
JBF1091	Manually settable Seat Tilt 0 - 15°	•
SEAT TO GRO	UND HEIGHT*	
JBF2857	Seat-to-Floor Height 435 mm	O
JBF2858	Seat-to-Floor Height 460 mm	O
JBF2859	Seat-to-Floor Height 485 mm	O
BACKREST RE	CLINER*	
JBF0975	Manual Settable Recliner (in 3.75° steps) 90° - 120°	•
FOOTREST HA	NGER TYPE*	
JBF0526	Standard hanger 80° pair Lower leg length: 350 - 450 mm	•
FOOTPLATE T		
JBF0512	Fixed Footplate pair	•

CONTROLS*		
JBF2204	Remote LiNX DLX-REM216 = Drive, Actuators & Lights 3 Drive functions and power module incl. 2 Actuators & Lights	•
CONTROL BE	RACKETRY*	
JBF1707	Swing Away Bracket RH	•
JBF1708	Swing Away Bracket LH	O
SHROUD CO	DLOUR*	
JBF2871	Mid range - Black/Anthracite Shroud	O
JBF2872	Mid range - Silver Shroud	0
JBF2873	Mid range - Bengal Red Shroud	0
JBF2874	Mid range - Mercury Blue Shroud	0
JBF2875	Mid range - Midnight Purple Shroud	O
RIM COLOUR	R*	
JBF2882	Mid range - Black Rim Inserts	•
JBF2883	Mid range - Silver Rim Inserts	O
JBF2884	Mid range - Bengal Red Rim Inserts	O
JBF2885	Mid range - Mercury Blue Rim Inserts	O
JBF2886	Mid range - Midnight Purple Rim Inserts	O
FORKS*		
JBF2632	Double sided fork Without castor rim insert (enlarges wide base to 656 mm)	♦
FRONT WHE	EL*	
JBF0836	9" (225 mm) x 2.80 (70 mm) Castor, puncture proof solid tyre	♦
DRIVE WHEE	EL*	
JBF0705	DW 14" (355 mm) x 3" (75 mm), Solid inlay Dual density foam insert	♦
C.T.C SUSPE	ENSION*	
JBF2870	CTC Suspension Control - Traction - Comfort	•
SUSPENSION	N SETTING*	
JBF1910	Soft (suggested for up to 70 kg User Weight)	O
JBF1912	Medium (suggested for up to 90 kg User Weight)	0
JBF1911	Firm (suggested for up to 110 kg User Weight)	0
JBF1915	Very firm (suggested for up to 136 kg User Weight)	0
MOTOR TYPE	E*	
JBF1909	12 km/h Ultra High Speed Package Always combined with LED Light system with Indicators, 30 Lux headlights	•
BATTERY TY	YPE*	
JBF1260	73,5 Ah Gel	•
CHARGER*		
JBF1343	Opti Charge Charger 8A (IP44)	•
ANTI-TIPPER	RS*	
JBF1205	Anti-tipper	♦
TRANSPORT	TATION KIT*	
JBF1494	4-Point tie-down (Tested version for using wheelchair as a vehicle seat according to ISO 7176-19) Adequate headrest is compulsory	\
LAP BELT*		
JBF1329	Lap belt with Auto Lock Standard mount on backrest	•

REAR VIEW MIRROR*				
JBF1415		Rear view mirror RH	0	
JBF1339		Rear view mirror LH	0	

TOTAL PRICE	İ
TOTAL PRICE	İ