



Invacare Ltd
 Unit 4 Pencoed Technology Park
 Pencoed, Bridgend
 CF35 5AQ
 T: 01656 776222
 E: ordersuk@invacare.com
 www.invacare.co.uk



Please fill in all specifications with each order.

Account code
 Customer order number
 Company name
 Address

e-fix E35		£4571
Included as standard:	22"	24"
<ul style="list-style-type: none"> • 2 e-fix drive wheels • LED display unit • Mobility Plus package • Range 16km (10 miles) • Max. user weight 120kg • 6.0 Ah battery (2kg) • Wheel weight 7.8kg • Total weight 18.9kg 	7.5 Ah battery (2kg)	£235

e-fix E36		£5,300
Included as standard:	24"	
<ul style="list-style-type: none"> • 2 e-fix drive wheels • LED display unit • Mobility Plus package • Range 20km (12.4 miles) • Max. user weight 160kg • 7.5 Ah battery (2kg) • Wheel weight 8kg • Total weight 19.3kg 	6Ah battery (2kg)	-£235



Brackets required for installation onto wheelchair

1457841	£101
Omit brackets	

Fitting on wheelchair at Invacare factory & delivery*	£75
---	------------

Wheelchair order number



Collection & fitting to third party wheelchair & delivery**	£75 + £96
Fitting by trained dealer***	£0

Control Unit Mounting		
Right side		
Left side		
Right & Left (pluggable)		£67
Bracket on:	Frame tube	Side part

*Only when ordered with an Invacare wheelchair.
 **Pending compatibility
 ***Mounting kits can only be sent to selected trained dealers.

Wheelchair details

Wheelchair manufacturer (e.g. Kuschall)
 Serial no Year
 Model (e.g. Compact)

Seat width  cm
 Seat height (e.g. Hemi)  cm

Armrest & Brake type

Degree of wheel camber

(Drum brakes must be removed)

Do you want to use both your standard and e-fix wheels in the future? If so, please order the retrofit stub axle.

Manual wheel axle retrofit for e-fix * / **
Retrofit, stub axle to 1/2" diameter £103

*If the manual wheels are used in combination with e-fix, these must be fitted with 1/2" stub axles, without drum brakes and 1" wide tyres.
 **If drum brakes are installed, these must be removed as they are not compatible with e-fix. Standard lever brakes are used instead.



Accessories

Anti-tippers with jack-up function (pair)* 1489214 £281

Control Unit Accessories

Swivel arm 1467901 £357

Protection Bumper 1565836 £51

Joystick Options

Option special 40mm/1.57" 1565669 £27

Option soft 70mm/2.76" 1566196 £27

Option T - handle 1565670 £88

**NB Always use anti-tippers (Alber or existing)*

Tray table incl. control unit bracket

Control unit centered SW 38-43cm 1566207 £251

Control unit centered SW 43-48cm 1566208 £251

Installation kit for control unit with existing tray table 1566206 £148

Extension for speed pre-selection

Set for speed pre-selection 1566197 £41

Extension for coupling ring

Set for one drive wheel (single) 1566179 £103

Set for two drive wheels (pair) 1566178 £205

Spoke Covers (pair)

22" wheel, decor 'Alber' 1566201 £64

22" wheel, transparent 1566203 £64

24" wheel, decor 'Alber' 1566200 £64

24" wheel, transparent 1566202 £64

Attendant Control Bracket

Right 1457754 £125

Left 1457755 £125

Intuitive Attendant Control

Control unit intuitive attendant control 1566165 £458

Adapter cable intuitive attendant control 1566177 £97

Additional handle 1566166 £45

Opti-box 1566184 £352

Speed/Stop limit switch 1467698 £75

Battery pack

Spare battery 6.0 Ah 1565639 £553

Spare battery 7.5 Ah 1566153 £727

Transport bag for battery 1566168 £73

Attachment set for transport bag 1566169 £21

Battery holder fixation

Fixed assembly set for cross brace 1566164 £174

Fixed assembly set for cross tube 1566163 £150

Mobility Plus Package*

Allows the individual to connect to their smartphone via Bluetooth and access functions which include battery status, speed, range, drive mode. It also allows speed up to 8km/h, remote control function and on Android devices, the ability to monitor incoming phone calls and SMS via the e-fix display screen.

**iPhone and Android compatible.*


Other

External charger socket incl. clip 1566177 £97

Brake extension 1467780 £31

Rear wheel extension available

Available wheel position:



1=rear

2=centre

3=front

**NB Always use anti-tippers (Alber or existing)*

Comments (mounting etc.)