



Yes, you can:

Tel: 01656 776222
Email: ordersuk@invacare.com
Online Spares available at: www.invacare.co.uk

JULY 2025
Customer Ref:

Customer Ref*	Account No*
Contact No*	Order No*
Delivery Address*	Order Qty*
	Order date*

Emotion M25 or Duo Drive with Kuschall K series 2.0 M121 & M125 1001887 / 706258

Standard Features

- Max User Weight 130kg (20.5 stone)
- Crash Tested ISO 7176-Part 19
- Active Rigid Wheelchair with Height Adjustable Rigid Footrest
- Multiple adjustments, Front and Rear Seat Heights and Centre of Gravity
- Full Hydroformed Aluminium Front Frame 75° Front Angle
- 24" Self Propel Q/R Wheels with Grey Aluminium Handrims and Pneumatic Tyres
- 5 position rear wheel extension
- Choice of 10 Seat Widths 320mm to 500mm
- Choice of 8 Seat Depths 350mm to 525mm
- Range of Front Seat Heights from 450mm to 520mm
- Range of Rear Seat Heights from 390mm to 490mm
- Lockdown Folding, Angle and Height Adjustable Backrest
- Black Nylon with Reflective Trim, Tension Adjustable Upholstery
- Without Push Handles, Carbon Clothesguards
- Black Aluminium Axle Tube with 0° Camber
- Black Comfort Front Castor
- Standard Brake Lever Bent
- Tool Kit



Standard Base price: £8,802

Please make your selection with a cross in the box ☐ Free of charge ☒ standard feature POA special request

Customer weight = KG

Code Description

BASE PRODUCT*

DKA0067	☐	KÜSCHALL K-SERIES	☒
DKA9250	☐	E-Motion M25 Weekly Price £61.34 Including Anti tippers with Jack up function M121	£8,343
DKA9251	☐	E-Motion DuoDrive Weekly Price £63.48 Including Anti tippers with Jack up function M125	£8,802

FRAME*				
DKA1040		V Style Standard Frame Angle 75° Aluminium	(NC 1475, 1490, 1495)	◆
DKA1050		Tapered Style Standard Frame Angle 75° Aluminium	(NC 1475, 1490, 1495, 1740, 1745, 1750)	○
DKA1060		V Style +5cm Frame Angle 75° Aluminium. Frame to accommodate a longer seat depth and seat height for taller clients	(NC 1410, 1420, 1435, 1740, 1745, 1750, 1755, 1760)	○
DKA1070		V Style Standard Frame Angle 90° Aluminium	(NC 1475, 1490, 1495)	○
DKA1080		Tapered Style Standard Frame Angle 90° Aluminium. Taper before the frame bend creating a parallel style front frame with a wider footrest space	(NC 1475, 1490, 1495, 1740, 1745, 1750, 5300, 5350)	○
DKA1090		V Style +5cm Frame Angle 90° Aluminium. Frame to accommodate a longer seat depth and seat height for taller clients	(NC 1410, 1420, 1435, 1740, 1745, 1750, 1755, 1760)	○
SEAT WIDTH*				
DKA1310		320 mm	(NC 3420)	○
DKA1315		340 mm	(NC 3420)	○
DKA1320		360 mm		○
DKA1325		380 mm		○
DKA1330		400 mm		◆
DKA1335		420 mm		○
DKA1340		440 mm		○
DKA1345		460 mm		○
DKA1350		480 mm		○
DKA1355		500 mm		○
SEAT DEPTH*				
DKA1410		350 mm	(NC 1500, 1510)	○
DKA1420		375 mm		○
DKA1435		400 mm		◆
DKA1450		425 mm		○
DKA1465		450 mm		○
DKA1475		475 mm		○
DKA1490		500 mm		○
DKA1495		525 mm		○
SEAT POSITION. Seat module can be moved forward and backward along the frame to achieve a more active or stable rear wheel position*				
DKA1500		Position 1 = 140 mm MOST ACTIVE POSITION		○
DKA1510		Position 2 = 125 mm		○
DKA1520		Position 3 = 110 mm		◆
DKA1530		Position 4 = 95 mm		○
DKA1540		Position 5 = 80 mm LEAST ACTIVE POSITION		○

BACK HEIGHT. Transportation kit is only possible with backrest heights of 405mm and above*				
DKA1600		Back Height for 3rd party backrest. Final height depends on the height of the positioning backrest, select if Matrx/Fixed backrest is required.	(NC 2100, 2220)	☐
DKA1605		270 mm	(NC 2150, 2240)	☐
DKA1610		285 mm	(NC 2150, 2240)	☐
DKA1615		300 mm	(NC 2150, 2240)	☐
DKA1620		315 mm	(NC 2150, 2240)	☐
DKA1625		330 mm	(NC 2150, 2240)	☐
DKA1630		345 mm	(NC 2150, 2240)	☐
DKA1635		360 mm	(NC 2150, 2240)	☐
DKA1640		375 mm	(NC 2150, 2240)	☐
DKA1645		390 mm	(NC 2150, 2240)	☐
DKA1650		405 mm	(NC 2150, 2240)	☐
DKA1655		420 mm	(NC 2150, 2240)	☐
DKA1660		435 mm	(NC 2150, 2240)	☐
DKA1665		450 mm	(NC 2150, 2240)	☐
DKA1670		465 mm	(NC 2150, 2240)	☐
DKA1675		480 mm	(NC 2150, 2240)	☐
FRONT SEAT HEIGHT. For 75° frames, the maximum lower leg must be front seat height minus 30mm and minus 40mm for 90° frames*				
DKA1740		450 mm	(NC 5300, 5350)	☐
DKA1745		460 mm	(NC 5300, 5350)	☐
DKA1750		470 mm		☐
DKA1755		480 mm		☐
DKA1760		490 mm		☐
DKA1765		500 mm		☒
DKA1770		510 mm		☐
DKA1775		520 mm		☐
REAR SEAT HEIGHT*				
DKA1815		390 mm	(NC 6040)	☐
DKA1820		400 mm	(NC 6040)	☐
DKA1825		410 mm		☐
DKA1830		420 mm		☐
DKA1835		430 mm		☐
DKA1840		440 mm		☒
DKA1845		450 mm		☐
DKA1850		460 mm		☐
DKA1855		470 mm		☐
DKA1860		480 mm		☐
DKA1865		490 mm	(NC 6410)	☐

LOWER LEG LENGTH. Cushion height must be deducted*			
DKA1918		290 mm	○
DKA1920		300 mm	○
DKA1922		310 mm	○
DKA1924		320 mm	○
DKA1926		330 mm	○
DKA1928		340 mm	○
DKA1930		350 mm	○
DKA1932		360 mm	○
DKA1934		370 mm	○
DKA1936		380 mm	○
DKA1938		390 mm	○
DKA1940		400 mm	○
DKA1942		410 mm	○
DKA1944		420 mm	○
DKA1946		430 mm	◆
DKA1948		440 mm	○
DKA1950		450 mm	○
DKA1952		460 mm	○
DKA1954		470 mm	○
DKA1956		480 mm	○
BACKREST MATERIAL*			
DKA2000		Aluminium	◆
BACKREST TYPE*			
DKA2100		Standard Backrest with Backbrace, lockdown folding for easy transportation (NC 2240)	◆
DKA2150		Backrest with Lower Backbrace for use with Matrx fixed back. Backrest Tube Height is 285 mm, lockdown folding for easy transportation (NC 2220)	○
BACKREST UPHOLSTERY*			
DKA2220		Tension Adjustable Backrest, with Premium Black Nylon and Reflective Trim Upholstery Cover, Back Pocket/hook and loop fastener	◆
DKA2240		Without Backrest Upholstery Select if fitting a Matrx/Fixed backrest, no upholstery required	○
PUSH HANDLES*			
DKA2400		Without Push Handles	◆
BACKREST ANGLE*			
DKA2520		78° angle from the seat	○
DKA2540		82° angle from the seat	○
DKA2560		86° angle from the seat	○
DKA2580		90° angle from the seat	◆
DKA2590		94° angle from the seat	○
SEAT UPHOLSTERY*			
DKA2600		Standard Nylon Seat Upholstery with one 5cm central band (Loop)	◆
FOOTREST*			
DKA3200		Footrest Tube, Rigid - Aluminium Hydroformed Profile	◆

CALF STRAP*			
DKA3300		Calf strap mounted on the frame with hook and loop	◆
DKA3305		Calf strap mounted with bracket support	○
CLOTHESGUARDS/MUDGUARDS*			
DKA3420		Carbon Clothesguards, Flip up, Fold in	◆
FRAME COLOUR*			
DKA4000		Space Black (RAL 9005)	○
DKA4010		Anthracite Grey (RAL 7016)	○
DKA4020		Pure White (RAL 9016) (NC 4220)	○
DKA4030		Carmine Red (RAL 3002)	○
DKA4040		Azure Blue (RAL 5017)	○
FRAME DECAL TYPE*			
DKA4195		Tag (Small Kuschall brand transfer on front of frame) (NC 4200, 4210, 4220, 4230, 4240, 4250, 2222)	◆
DKA4197		Without Tag (Kuschall branding only) (NC 4200, 4210, 4220, 4230, 4240, 4250, 4300, 4310)	○
BOLD DECAL COLOUR*			
DKA4200		Black	○
DKA4210		Dark Grey	○
DKA4220		Light Grey	○
DKA4230		Red	○
DKA4240		Blue	○
DKA4250		Gold	○
DKA1111		No bold colour, select only with Option DKA4195 Tag or DKA4197 Without Tag	○
TAG COLOUR*			
DKA4300		Black	○
DKA4310		Red	○
DKA2222		No tag colour, select only with Option DKA4190 Bold Decal or DKA4197 Without Tag (NC 4195)	○
FRONT CASTORS*			
DKA5000		75mm x 25mm (3" x 1") Supersport	○
DKA5050		100mm x 30mm (4" x 1.2") Everyday Black hub and tyre	○
DKA5100		100mm x 30mm (4" x 1.2") Comfort Black hub and tyre	○
DKA5300		125mm x 30mm (5" x 1.2") Everyday Black hub and tyre	○
DKA5350		125mm x 30mm (5" x 1.2") Comfort Black hub and tyre	○
REAR WHEEL POSITION*			
DKA6020		Standard, Fixed Rear Wheel Position (NC 6100, 6110, 6120, 6130, 6140)	◆
DKA6040		Rear Wheel Extension (5 Positions)	◆
CAMBER AXLE TYPE*			
DKA6060		Standard Aluminium Axle	◆
POSITION OF AXLE			
DKA6100		1st Position from the front. If 2nd axle is selected, 1st axle must be placed in 1st position and 2nd in the 5th position	○
DKA6110		2nd Position from the front	○
DKA6120		3rd Position from the front	○
DKA6130		4th Position from the front	○
DKA6140		5th Position from the front	○

CAMBER ANGLE*			
DKA6200	☐	0° Camber	◆
REAR WHEEL SIZE*			
DKA6410	☐	24"	◆
REAR WHEEL TYPE*			
DKA6510	☐	24", 26" Kuschall Starec Wheel, 24" Black Cross Spokes, Rim & Hub. 26" Silver Cross-Spokes, Colourless hub and Black rim	◆
REAR WHEEL TYRE*			
DKA6600	☐	24" Maxxis Lite guard Pneumatic tyre. Herringbone tread, Silvershield puncture protection	◆
HANDRIM*			
DKA6780	☐	24", 25", 26" Light Aluminium Grey, long tab with 2 holes for 3 cm or 4cm mountings, mounted at 3cm distance	◆
BRAKES*			
DKA7210	☐	Standard Push to Lock Brakes, Lever Bent	◆
OTHER OPTIONS			
DKA8550	☐	Tool Kit	◆

			TOTAL PRICE	
--	--	--	-------------	----------------------

Non Conforming Options:

DKA1410	350 mm
DKA1420	375 mm
DKA1435	400 mm
DKA1475	475 mm
DKA1490	500 mm
DKA1495	525 mm
DKA1500	Position 1 = 140 mm MOST ACTIVE POSITION
DKA1510	Position 2 = 125 mm
DKA1740	450 mm
DKA1745	460 mm
DKA1750	470 mm
DKA1755	480 mm
DKA1760	490 mm
DKA2100	Standard Backrest with Backbrace, lockdown folding for easy transportation
DKA2150	Backrest with Lower Backbrace for use with Matrix fixed back. Backrest Tube Height is 285 mm, lockdown folding for easy transportation
DKA2220	Tension Adjustable Backrest, with Premium Black Nylon and Reflective Trim Upholstery Cover, Back Pocket/hook and loop fastener
DKA2240	Without Backrest Upholstery Select if fitting a Matrix/Fixed backrest, no upholstery required
DKA3420	Carbon Clothesguards, Flip up, Fold in
DKA4195	Tag (Small Kuschall brand transfer on front of frame)
DKA4200	Black
DKA4210	Dark Grey
DKA4220	Light Grey
DKA4230	Red
DKA4240	Blue
DKA4250	Gold
DKA4300	Black
DKA4310	Red
DKA2222	No tag colour, select only with Option DKA4190 Bold Decal or DKA4197 Without Tag
DKA5300	125mm x 30mm (5" x 1.2") Everyday Black hub and tyre
DKA5350	125mm x 30mm (5" x 1.2") Comfort Black hub and tyre
DKA6040	Rear Wheel Extension (5 Positions)
DKA6100	1st Position from the front. If 2nd axle is selected, 1st axle must be placed in 1st position and 2nd in the 5th position
DKA6110	2nd Position from the front
DKA6120	3rd Position from the front
DKA6130	4th Position from the front
DKA6140	5th Position from the front
DKA6410	24"



For a more complex customer requirement
please refer to our Invacare Unique special order form.
email specialsuk@invacare.com

Special Instructions

Please supply the following information:

Name:

Email:

Phone:

Description of special request (please include relevant option code or part number):