



**Yes, you can:**

Tel: 01656 776222  
Email: [ordersuk@invacare.com](mailto:ordersuk@invacare.com)  
Online Spares available at: [www.invacare.co.uk](http://www.invacare.co.uk)

# Motability Retail Prescription Form

February 2026  
Customer Ref:

<b>Customer Ref*</b>	<b>Account No*</b>
<b>Contact No*</b>	<b>Order No*</b>
<b>Delivery Address*</b>	<b>Order Qty*</b>
	<b>Order date*</b>

## AVIVA RX20 Modulite M22 707038 - Weekly Price £54.44

### Standard Features

- Max user weight 136kg (21 Stone)
- Crash tested ISO 7176 -Part 19
- Modulite seating system
- Flex3 adjustable Backrest Plates with Laguna Backrest cushion
- Standard T-Armrests, detachable with long armpad
- Neckrest depth adjustable
- Powered "fixed pivot" Tilt 20°
- Manual Settable Recliner (in 3.75° steps) 90° - 120°
- 80° hangers with fixed footplate
- Remote LiNX DLX-REM211 with swing away bracket
- 8" Castor, puncture proof solid tyre
- Solid inlay black drive wheels
- 6 km/h 4mph motors
- 60Ah batteries
- Anti tippers
- 4 Point tie down system
- Lapbelt with autolock (adjustable both sides)

**Standard Base price: £6,462**



Please make your selection with a cross in the box    ☐ Free of charge    ☒ standard feature    POA    special request

Customer weight =                      KG

Code	Description	
<b>BASE MODEL*</b>		
JBC0000	<input type="checkbox"/> AVIVA RX 20 Base Model Max user weight up to 136 kg	£6,462
<b>CHASSIS WIDTH*</b>		
JBL2810	<input type="checkbox"/> Chassis Narrow (560 mm/22")	◆
<b>SEATING TYPE*</b>		
JBC2100	<input type="checkbox"/> Invacare® Modulite Seat Unit	◆
<b>SEAT FRAME*</b>		
JBC2111	<input type="checkbox"/> Telescopic Seat Frame and Plate with Side Rails	◆

SEAT WIDTH*			
JBC2121	<input type="checkbox"/>	380 mm Seat Plate	<input type="radio"/>
JBC2122	<input type="checkbox"/>	430 mm Seat Plate	<input type="radio"/>
JBC2123	<input type="checkbox"/>	480 mm Seat Plate	<input type="radio"/>
JBC2124	<input type="checkbox"/>	530 mm Seat Plate	<input type="radio"/>
SEAT DEPTH*			
JBC2132	<input type="checkbox"/>	Seat Depth 410 mm	<input type="radio"/>
JBC2134	<input type="checkbox"/>	Seat Depth 460 mm	<input type="radio"/>
JBC2136	<input type="checkbox"/>	Seat Depth 510 mm	<input type="radio"/>
SEAT CUSHION*			
JBC2142	<input type="checkbox"/>	Matrx Flo-tech Cushion Flo-tech Lite	<input checked="" type="radio"/>
BACKREST SUPPORT*			
JBC2162	<input type="checkbox"/>	Backposts tall (540 mm)	<input checked="" type="radio"/>
PUSH HANDLES FOR BACKPOSTS			
JBC2108	<input type="checkbox"/>	Backposts without push handles	<input checked="" type="radio"/>
BACKREST UPHOLSTERY / CUSHION*			
JBC2173	<input type="checkbox"/>	Flex3 adjustable Backrest Plates with Laguna Backrest cushion	<input checked="" type="radio"/>
UPHOLSTERY TYPE*			
JBC2152	<input type="checkbox"/>	Black Black multi stretch PU coated fabric Upholstery	<input type="radio"/>
JBC2155	<input type="checkbox"/>	Black Spacer Fabric Upholstery	<input type="radio"/>
ARMREST (Pair)*			
JBC2191	<input type="checkbox"/>	T-Arm detachable, Standard	<input checked="" type="radio"/>
ARMPAD (Pair)*			
JBC2196	<input type="checkbox"/>	Long Armpad (375 mm)	<input checked="" type="radio"/>
HEADREST / NECKREST (Adequate headrest option must be selected)*			
JBC1350	<input type="checkbox"/>	Neckrest depth adjustable	<input checked="" type="radio"/>
MANUAL / POWERED SEATING OPTIONS*			
JBC1092	<input type="checkbox"/>	Powered "fixed pivot" Tilt 20°	<input checked="" type="radio"/>
SEAT TO GROUND HEIGHT*			
JBC2857	<input type="checkbox"/>	Seat-to-Floor Height 435 mm	<input type="radio"/>
JBC2858	<input type="checkbox"/>	Seat-to-Floor Height 460 mm	<input type="radio"/>
JBC2859	<input type="checkbox"/>	Seat-to-Floor Height 485 mm	<input type="radio"/>
BACKREST RECLINER*			
JBC0975	<input type="checkbox"/>	Manual Settable Recliner (in 3.75° steps) 90° - 120°	<input checked="" type="radio"/>
LEG REST TYPE*			
JBC0526	<input type="checkbox"/>	Standard hanger 80° pair Lower leg length: 350 - 450 mm	<input checked="" type="radio"/>
FOOTPLATE TYPE*			
JBC0512	<input type="checkbox"/>	Fixed Footplate pair	<input checked="" type="radio"/>
LiNX CONTROLS*			
JBC2203	<input type="checkbox"/>	Remote LiNX DLX-REM211 = Drive & Actuators 3 Drive functions and power module incl. 2 Actuators	<input checked="" type="radio"/>
CONTROL BRACKETRY*			
JBC1707	<input type="checkbox"/>	Swing Away Bracket RH	<input type="radio"/>
JBC1708	<input type="checkbox"/>	Swing Away Bracket LH	<input type="radio"/>

SHROUD COLOUR*			
JBC2871	<input type="checkbox"/>	Mid range - Black/Anthracite Shroud	<input type="radio"/>
JBC2872	<input type="checkbox"/>	Mid range - Silver Shroud	<input type="radio"/>
JBC2873	<input type="checkbox"/>	Mid range - Bengal Red Shroud	<input type="radio"/>
JBC2874	<input type="checkbox"/>	Mid range - Mercury Blue Shroud	<input type="radio"/>
JBC2875	<input type="checkbox"/>	Mid range - Midnight Purple Shroud	<input type="radio"/>
RIM COLOUR*			
JBC2882	<input type="checkbox"/>	Mid range - Black Rim Inserts	<input type="radio"/>
JBC2883	<input type="checkbox"/>	Mid range - Silver Rim Inserts	<input type="radio"/>
JBC2884	<input type="checkbox"/>	Mid range - Bengal Red Rim Inserts	<input type="radio"/>
JBC2885	<input type="checkbox"/>	Mid range - Mercury Blue Rim Inserts	<input type="radio"/>
JBC2886	<input type="checkbox"/>	Mid range - Midnight Purple Rim Inserts	<input type="radio"/>
FORKS*			
JBC2632	<input type="checkbox"/>	Double sided fork Without castor rim insert (enlarges wide base to 656 mm)	<input checked="" type="radio"/>
CASTORS*			
JBC0828	<input type="checkbox"/>	8" (200 mm) x 2.50-4 (65 mm) Castor, puncture proof solid tyre	<input checked="" type="radio"/>
DRIVE WHEELS*			
JBC0705	<input type="checkbox"/>	DW 14" (355 mm) x 3" (75 mm), Solid inlay Dual density foam insert	<input checked="" type="radio"/>
C.T.C SUSPENSION*			
JBC2870	<input type="checkbox"/>	CTC Suspension Control - Traction - Comfort	<input checked="" type="radio"/>
SUSPENSION SETTING*			
JBC1910	<input type="checkbox"/>	Soft (suggested for up to 70 kg User Weight)	<input type="radio"/>
JBC1912	<input type="checkbox"/>	Medium (suggested for up to 90 kg User Weight)	<input type="radio"/>
JBC1911	<input type="checkbox"/>	Firm (suggested for up to 110 kg User Weight)	<input type="radio"/>
JBC1915	<input type="checkbox"/>	Very firm (suggested for up to 136 kg User Weight)	<input type="radio"/>
MOTOR TYPE*			
JBC1282	<input type="checkbox"/>	6 km/h	<input checked="" type="radio"/>
BATTERY TYPE*			
JBC1259	<input type="checkbox"/>	60 Ah Gel	<input checked="" type="radio"/>
CHARGER*			
JBC1343	<input type="checkbox"/>	Opti Charge Charger 8A (IP44)	<input checked="" type="radio"/>
ANTI-TIPPERS*			
JBC1205	<input type="checkbox"/>	Anti-tipper	<input checked="" type="radio"/>
TRANSPORTATION KIT*			
JBC1494	<input type="checkbox"/>	4-Point tie-down (Tested version for using wheelchair as a vehicle seat according to ISO 7176-19) Adequate headrest is compulsory	<input checked="" type="radio"/>
LAP BELT*			
JBC2113	<input type="checkbox"/>	Lap belt with Auto Lock Flexible mount in side rails	<input checked="" type="radio"/>

TOTAL PRICE			
-------------	--	--	--

Non Conforming Options:



For a more complex customer requirement,  
please email: [orders@invacare.com.au](mailto:orders@invacare.com.au)

Special Instructions

Please supply the following information:

Name:

Email:

Phone:

Description of special request (please include relevant option code or part number):