



# Motability Retail Prescription Form

**Yes, you can:**

Tel: 01656 776222  
Email: [ordersuk@invacare.com](mailto:ordersuk@invacare.com)  
Online Spares available at: [www.invacare.co.uk](http://www.invacare.co.uk)

January 2026  
Customer Ref:

<b>Customer Ref*</b>	<b>Account No*</b>
<b>Contact No*</b>	<b>Order No*</b>
<b>Delivery Address*</b>	<b>Order Qty*</b>
	<b>Order date*</b>

## Emotion M25 or Duo Drive with Kuschall K series 2.0 M121 & M125 1001887 / 706258

### Standard Features

- Max User Weight 130kg (20.5 stone)
- Crash Tested ISO 7176-Part 19
- Active Rigid Wheelchair with Height Adjustable Rigid Footrest
- Multiple adjustments, Front and Rear Seat Heights and Centre of Gravity
- Full Hydroformed Aluminium Front Frame 75° Front Angle
- 24" Self Propel Q/R Wheels with Grey Aluminium Handrims and Pneumatic Tyres
- 5 position rear wheel extension
- Choice of 10 Seat Widths 320mm to 500mm
- Choice of 8 Seat Depths 350mm to 525mm
- Range of Front Seat Heights from 450mm to 520mm
- Range of Rear Seat Heights from 390mm to 490mm
- Lockdown Folding, Angle and Height Adjustable Backrest
- Black Nylon with Reflective Trim, Tension Adjustable Upholstery
- Without Push Handles, Carbon Clothesguards
- Black Aluminium Axle Tube with 0° Camber
- Black Comfort Front Castor
- Standard Brake Lever Bent
- Tool Kit

**Standard Base price: £8,802**



Please make your selection with a cross in the box       Free of charge       standard feature       POA special request

Customer weight =      KG

### Code      Description

<b>BASE PRODUCT*</b>		
DKA0067	KÜSCHALL K-SERIES	◆
DKA9250	E-Motion M25 Weekly Price £67.27 Including Anti tippers with Jack up function M122	£8,343
DKA9251	E-Motion DuoDrive Weekly Price £68.59 Including Anti tippers with Jack up function M126	£8,802

**FRAME\***

DKA1040	V Style Standard Frame Angle 75° Aluminium	(NC 1475, 1490, 1495)	◆
DKA1050	Tapered Style Standard Frame Angle 75° Aluminium	(NC 1475, 1490, 1495, 1740, 1745, 1750)	○
DKA1060	V Style +5cm Frame Angle 75° Aluminium. Frame to accommodate a longer seat depth and seat height for taller clients	(NC 1410, 1420, 1435, 1740, 1745, 1750, 1755, 1760)	○
DKA1070	V Style Standard Frame Angle 90° Aluminium	(NC 1475, 1490, 1495)	○
DKA1080	Tapered Style Standard Frame Angle 90° Aluminium. Taper before the frame bend creating a parallel style front frame with a wider footrest space	(NC 1475, 1490, 1495, 1740, 1745, 1750, 5300, 5350)	○
DKA1090	V Style +5cm Frame Angle 90° Aluminium. Frame to accommodate a longer seat depth and seat height for taller clients	(NC 1410, 1420, 1435, 1740, 1745, 1750, 1755, 1760)	○

**SEAT WIDTH\***

DKA1310	320 mm	(NC 3420)	○
DKA1315	340 mm	(NC 3420)	○
DKA1320	360 mm		○
DKA1325	380 mm		○
DKA1330	400 mm		◆
DKA1335	420 mm		○
DKA1340	440 mm		○
DKA1345	460 mm		○
DKA1350	480 mm		○
DKA1355	500 mm		○

**SEAT DEPTH\***

DKA1410	350 mm	(NC 1500, 1510)	○
DKA1420	375 mm		○
DKA1435	400 mm		◆
DKA1450	425 mm		○
DKA1465	450 mm		○
DKA1475	475 mm		○
DKA1490	500 mm		○
DKA1495	525 mm		○

**SEAT POSITION. Seat module can be moved forward and backward along the frame to achieve a more active or stable rear wheel position\***

DKA1500	Position 1 = 140 mm MOST ACTIVE POSITION	○
DKA1510	Position 2 = 125 mm	○
DKA1520	Position 3 = 110 mm	◆
DKA1530	Position 4 = 95 mm	○
DKA1540	Position 5 = 80 mm LEAST ACTIVE POSITION	○

**BACK HEIGHT. Transportation kit is only possible with backrest heights of 405mm and above\***

DKA1600		Back Height for 3rd party backrest. Final height depends on the height of the positioning backrest, select if Matrix/Fixed backrest is required.	(NC 2100, 2220)	<input type="radio"/>
DKA1605		270 mm	(NC 2150, 2240)	<input type="radio"/>
DKA1610		285 mm	(NC 2150, 2240)	<input type="radio"/>
DKA1615		300 mm	(NC 2150, 2240)	<input type="radio"/>
DKA1620		315 mm	(NC 2150, 2240)	<input type="radio"/>
DKA1625		330 mm	(NC 2150, 2240)	<input type="radio"/>
DKA1630		345 mm	(NC 2150, 2240)	<input type="radio"/>
DKA1635		360 mm	(NC 2150, 2240)	<input type="radio"/>
DKA1640		375 mm	(NC 2150, 2240)	<input type="radio"/>
DKA1645		390 mm	(NC 2150, 2240)	<input type="radio"/>
DKA1650		405 mm	(NC 2150, 2240)	<input type="radio"/>
DKA1655		420 mm	(NC 2150, 2240)	<input type="radio"/>
DKA1660		435 mm	(NC 2150, 2240)	<input type="radio"/>
DKA1665		450 mm	(NC 2150, 2240)	<input type="radio"/>
DKA1670		465 mm	(NC 2150, 2240)	<input type="radio"/>
DKA1675		480 mm	(NC 2150, 2240)	<input type="radio"/>

**FRONT SEAT HEIGHT. For 75° frames, the maximum lower leg must be front seat height minus 30mm and minus 40mm for 90° frames\***

DKA1740		450 mm	(NC 5300, 5350)	<input type="radio"/>
DKA1745		460 mm	(NC 5300, 5350)	<input type="radio"/>
DKA1750		470 mm		<input type="radio"/>
DKA1755		480 mm		<input type="radio"/>
DKA1760		490 mm		<input type="radio"/>
DKA1765		500 mm		<input checked="" type="radio"/>
DKA1770		510 mm		<input type="radio"/>
DKA1775		520 mm		<input type="radio"/>

**REAR SEAT HEIGHT\***

DKA1815		390 mm	(NC 6040)	<input type="radio"/>
DKA1820		400 mm	(NC 6040)	<input type="radio"/>
DKA1825		410 mm		<input type="radio"/>
DKA1830		420 mm		<input type="radio"/>
DKA1835		430 mm		<input type="radio"/>
DKA1840		440 mm		<input checked="" type="radio"/>
DKA1845		450 mm		<input type="radio"/>
DKA1850		460 mm		<input type="radio"/>
DKA1855		470 mm		<input type="radio"/>
DKA1860		480 mm		<input type="radio"/>
DKA1865		490 mm	(NC 6410)	<input type="radio"/>

**LOWER LEG LENGTH. Cushion height must be deducted\***

DKA1918	290 mm	<input type="radio"/>
DKA1920	300 mm	<input type="radio"/>
DKA1922	310 mm	<input type="radio"/>
DKA1924	320 mm	<input type="radio"/>
DKA1926	330 mm	<input type="radio"/>
DKA1928	340 mm	<input type="radio"/>
DKA1930	350 mm	<input type="radio"/>
DKA1932	360 mm	<input type="radio"/>
DKA1934	370 mm	<input type="radio"/>
DKA1936	380 mm	<input type="radio"/>
DKA1938	390 mm	<input type="radio"/>
DKA1940	400 mm	<input type="radio"/>
DKA1942	410 mm	<input type="radio"/>
DKA1944	420 mm	<input type="radio"/>
DKA1946	430 mm	<input checked="" type="radio"/>
DKA1948	440 mm	<input type="radio"/>
DKA1950	450 mm	<input type="radio"/>
DKA1952	460 mm	<input type="radio"/>
DKA1954	470 mm	<input type="radio"/>
DKA1956	480 mm	<input type="radio"/>

**BACKREST MATERIAL\***

DKA2000	Aluminium	<input checked="" type="radio"/>
---------	-----------	----------------------------------

**BACKREST TYPE\***

DKA2100	Standard Backrest with Backbrace, lockdown folding for easy transportation	<input checked="" type="radio"/>
DKA2150	Backrest with Lower Backbrace for use with Matrix fixed back. Backrest Tube Height is 285 mm, lockdown folding for easy transportation	<input type="radio"/>

**BACKREST UPHOLSTERY\***

DKA2220	Tension Adjustable Backrest, with Premium Black Nylon and Reflective Trim Upholstery Cover, Back Pocket/hook and loop fastener	<input checked="" type="radio"/>
DKA2240	Without Backrest Upholstery Select if fitting a Matrix/Fixed backrest, no upholstery required	<input type="radio"/>

**PUSH HANDLES\***

DKA2400	Without Push Handles	<input checked="" type="radio"/>
---------	----------------------	----------------------------------

**BACKREST ANGLE\***

DKA2520	78° angle from the seat	<input type="radio"/>
DKA2540	82° angle from the seat	<input type="radio"/>
DKA2560	86° angle from the seat	<input type="radio"/>
DKA2580	90° angle from the seat	<input checked="" type="radio"/>
DKA2590	94° angle from the seat	<input type="radio"/>

**SEAT UPHOLSTERY\***

DKA2600	Standard Nylon Seat Upholstery with one 5cm central band (Loop)	<input checked="" type="radio"/>
---------	---	----------------------------------

**FOOTREST\***

DKA3200	Footrest Tube, Rigid - Aluminium Hydroformed Profile	<input checked="" type="radio"/>
---------	--	----------------------------------

**CALF STRAP\***

DKA3300	<input type="checkbox"/>	Calf strap mounted on the frame with hook and loop	◆
DKA3305	<input type="checkbox"/>	Calf strap mounted with bracket support	○

**CLOTHESGUARDS/MUDGUARDS\***

DKA3420	<input type="checkbox"/>	Carbon Clothesguards, Flip up, Fold in	◆
---------	--------------------------	--	---

**FRAME COLOUR\***

DKA4000	<input type="checkbox"/>	Space Black (RAL 9005)	○
DKA4010	<input type="checkbox"/>	Anthracite Grey (RAL 7016)	○
DKA4020	<input type="checkbox"/>	Pure White (RAL 9016)	○
DKA4030	<input type="checkbox"/>	Carmine Red (RAL 3002)	○
DKA4040	<input type="checkbox"/>	Azure Blue (RAL 5017)	○

**FRAME DECAL TYPE\***

DKA4195	<input type="checkbox"/>	Tag (Small Küschall brand transfer on front of frame)	(NC 2222)	◆
DKA4197	<input type="checkbox"/>	Without Tag (Kuschall branding only)	(NC 4300, 4310)	○

**TAG COLOUR\***

DKA4300	<input type="checkbox"/>	Black	○	
DKA4310	<input type="checkbox"/>	Red	○	
DKA2222	<input type="checkbox"/>	No tag colour, select only with Option DKA4197 Without Tag	(NC 4195)	○

**FRONT CASTORS\***

DKA5000	<input type="checkbox"/>	75mm x 25mm (3" x 1") Supersport	○
DKA5050	<input type="checkbox"/>	100mm x 30mm (4" x 1.2") Everyday Black hub and tyre	○
DKA5100	<input type="checkbox"/>	100mm x 30mm (4" x 1.2") Comfort Black hub and tyre	○
DKA5300	<input type="checkbox"/>	125mm x 30mm (5" x 1.2") Everyday Black hub and tyre	○
DKA5350	<input type="checkbox"/>	125mm x 30mm (5" x 1.2") Comfort Black hub and tyre	○

**REAR WHEEL POSITION\***

DKA6020	<input type="checkbox"/>	Standard, Fixed Rear Wheel Position	(NC 6100, 6110, 6120, 6130, 6140)	◆
DKA6040	<input type="checkbox"/>	Rear Wheel Extension (5 Positions)		◆

**CAMBER AXLE TYPE\***

DKA6060	<input type="checkbox"/>	Standard Aluminium Axle	◆
---------	--------------------------	-------------------------	---

**POSITION OF AXLE**

DKA6100	<input type="checkbox"/>	1st Position from the front. If 2nd axle is selected, 1st axle must be placed in 1st position and 2nd in the 5th position	○
DKA6110	<input type="checkbox"/>	2nd Position from the front	○
DKA6120	<input type="checkbox"/>	3rd Position from the front	○
DKA6130	<input type="checkbox"/>	4th Position from the front	○
DKA6140	<input type="checkbox"/>	5th Position from the front	○

**CAMBER ANGLE\***

DKA6200	<input type="checkbox"/>	0° Camber	◆
---------	--------------------------	-----------	---

**REAR WHEEL SIZE\***

DKA6410	<input type="checkbox"/>	24"	◆
---------	--------------------------	-----	---

**REAR WHEEL TYPE\***

DKA6510	<input type="checkbox"/>	24", 26" Küschall Starec Wheel, 24" Black Cross Spokes, Rim & Hub. 26" Silver Cross-Spokes, Colourless hub and Black rim	◆
---------	--------------------------	--	---

**REAR WHEEL TYRE\***

DKA6600	<input type="checkbox"/>	24" Maxxis Lite guard Pneumatic tyre. Herringbone tread, Silvershield puncture protection	◆
---------	--------------------------	--	---

**HANDRIM\***

DKA6780	<input type="checkbox"/>	24", 25", 26" Light Aluminium Grey, long tab with 2 holes for 3 cm or 4cm mountings, mounted at 3cm distance	<input checked="" type="checkbox"/>
---------	--------------------------	--	-------------------------------------

**BRAKES\***

DKA7210	<input type="checkbox"/>	Standard Push to Lock Brakes, Lever Bent	<input checked="" type="checkbox"/>
---------	--------------------------	--	-------------------------------------

**OTHER OPTIONS**

DKA8550	<input type="checkbox"/>	Tool Kit	<input checked="" type="checkbox"/>
---------	--------------------------	----------	-------------------------------------

	<b>TOTAL PRICE</b>	
--	--------------------	--

**Non Conforming Options:**

DKA1410	350 mm
DKA1420	375 mm
DKA1435	400 mm
DKA1475	475 mm
DKA1490	500 mm
DKA1495	525 mm
DKA1500	Position 1 = 140 mm MOST ACTIVE POSITION
DKA1510	Position 2 = 125 mm
DKA1740	450 mm
DKA1745	460 mm
DKA1750	470 mm
DKA1755	480 mm
DKA1760	490 mm
DKA2100	Standard Backrest with Backbrace, lockdown folding for easy transportation
DKA2150	Backrest with Lower Backbrace for use with Matrix fixed back. Backrest Tube Height is 285 mm, lockdown folding for easy transportation
DKA2220	Tension Adjustable Backrest, with Premium Black Nylon and Reflective Trim Upholstery Cover, Back Pocket/hook and loop fastener
DKA2240	Without Backrest Upholstery Select if fitting a Matrix/Fixed backrest, no upholstery required
DKA3420	Carbon Clothesguards, Flip up, Fold in
DKA4195	Tag (Small Küschall brand transfer on front of frame)
DKA4300	Black
DKA4310	Red
DKA2222	No tag colour, select only with Option DKA4197 Without Tag
DKA5300	125mm x 30mm (5" x 1.2") Everyday Black hub and tyre
DKA5350	125mm x 30mm (5" x 1.2") Comfort Black hub and tyre
DKA6040	Rear Wheel Extension (5 Positions)
DKA6100	1st Position from the front. If 2nd axle is selected, 1st axle must be placed in 1st position and 2nd in the 5th position
DKA6110	2nd Position from the front
DKA6120	3rd Position from the front
DKA6130	4th Position from the front
DKA6140	5th Position from the front
DKA6410	24"



For a more complex customer requirement,  
please email: [orders@invacare.com.au](mailto:orders@invacare.com.au)

**Special Instructions**

Please supply the following information:

Name:

Email:

Phone:

Description of special request (please include relevant option code or part number):